

OUTLANDER™ MAX

	SPECIFICATIONS	OUTLANDER MAX 400 EFI	OUTLANDER MAX 500 EFI XT™
ENGINE	Type	400cc, single cylinder, liquid-cooled, SOHC, 4-valve	499.6cc, V-twin, liquid-cooled, SOHC, 8-valve (4-valve/cyl)
	Bore & Stroke	91 x 61.5 mm	82 x 47 mm
ENGINE	Net Power	< 15kW (EC version only)	< 15kW (EC version only)
	Carburation/EFI	46 mm Throttle Body, Siemens VDO injector	46 mm Throttle Body, 2 Siemens VDO injectors
ENGINE	Starting System	Electric	Electric
	Transmission	CVT, sub-transmission with high, low, park, neutral & reverse	CVT, sub-transmission with high, low, park, neutral & reverse
ENGINE	Standard engine braking	Standard engine braking	Standard engine braking
	Drive Train	Selectable 2w/4w shaft driven with Visco-lok [†] front differential	Selectable 2w/4w shaft driven with Visco-lok front differential
ENGINE		Euro-2 approved	Euro-2 approved
CHASSIS	Frame	SST™	SST
	Front Suspension Type/Shocks	MacPherson [‡]	MacPherson
CHASSIS	Front Suspension Travel	178 mm (7 in)	178 mm (7 in)
	Rear Suspension Type/Shocks	TTI™ independent	TTI independent
CHASSIS	Rear Suspension Travel	203 mm (8 in)	229 mm (9 in)
	Front Brake	2 inboard hydraulic discs	2 inboard hydraulic discs
CHASSIS	Rear Brake	1 inboard hydraulic disc	1 inboard hydraulic disc
	Tires/Front	635 x 203 x 305 mm	635 x 203 x 305 mm
CHASSIS		25 x 8 x 12 in	25 x 8 x 12 in
	Tires/Rear	635 x 279 x 305 mm	635 x 279 x 305 mm
CHASSIS		25 x 11 x 12 in	25 x 11 x 12 in
	Wheels	Steel	Cast aluminum
DIMENSIONS	L x W x H (mm)	2,387 x 1,168 x 1,143 mm	2,387 x 1,168 x 1,143 mm
	L x W x H (in)	94 x 46 x 45 in	94 x 46 x 45 in
DIMENSIONS	Wheelbase	1,447 mm (57 in)	1,499 mm (59 in)
	Seat Height	889 mm (35 in)	877 mm (34.5 in)
DIMENSIONS	Ground Clearance	236 mm (9.3 in)	279 mm (11 in)
	Dry Weight	308 kg (680 lbs)	319 kg (704 lbs)
DIMENSIONS	Towing Capacity	500 kg (1,100 lbs)	590 kg (1,300 lbs)
	Rack Capacity	Front: 45 kg (100 lbs) Rear: 90 kg (200 lbs)	Front: 45 kg (100 lbs) Rear: 90 kg (200 lbs)
DIMENSIONS	Storage	Rear storage 20L (5.3 US gal) CRS (Convertible Rack System)	Rear storage 20L (5.3 US gal) CRS (Convertible Rack System)
	Fuel Capacity	16.3L (4.3 US gal)	16.3L (4.3 US gal)
FEATURES	Instrumentation	Multi-function digital LCD gauge: Speedometer, tachometer (bar graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4x4 indicator, temperature and engine lights, fuel gauge, clock, auto shut off after 15 minutes	Multi-function digital LCD gauge: Speedometer, tachometer (bar graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4x4 indicator, temperature and engine lights, fuel gauge, clock, auto shut off after 15 minutes
	Anti-Theft System	D.E.S.S.™ (Digital Encoded Security System)	D.E.S.S. (Digital Encoded Security System)
FEATURES	Electrical	Prewired for winch	Prewired for winch
	Lighting	2 fender mounted headlamps (35W) with tail light/brake light	2 fender mounted headlamps (35W) with tail light/brake light
FEATURES	DC Outlet	Lighter type in console, standard connector in the back (15A)	Lighter type in console, standard connector in the back (15A)
	Warning Signal	Horn	Horn
AVAILABLE PACKAGES	Color Available	Viper Red	
	XT PACKAGE CONTENT	XT cast aluminum wheels BRP XL3000 winch with roller fairlead and wired remote control Aggressive Carlisle [‡] ACT Radial tires Heavy-duty front & rear bumpers Handlebar wind deflectors	Dual-mode Dynamic Power Steering (DPS™) Visco-Lok QE XT cast aluminum wheels 650 watts magneto BRP XL3000 winch with roller fairlead and wired remote control Aggressive Carlisle ACT Radial tires Heavy-duty front & rear bumpers Handlebar wind deflectors
AVAILABLE PACKAGES	Color available for XT	Yellow	Yellow



OUTLANDER MAX 400 EFI



OUTLANDER MAX 400 EFI XT



OUTLANDER MAX 500 EFI XT

■ EC versions features

© 2010 Bombardier Recreational Products Inc (BRP). All rights reserved. ®, ™ and the BRP logo are registered trademarks of BRP or its affiliates. †Visco-Lok is a trademark of GKN ViscoDrive GmbH. ‡All other trademarks are the property of their respective owners. Specifications for EC homologated units may differ slightly from specifications mentioned herein. Some models, tires and accessories depicted may not be available in your country. Depending on location, products are distributed by BRP European Distribution SA, BRP US Inc., BRP Australia Pty Ltd, or Bombardier Recreational Products Inc. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at any time to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Some models depicted may include optional equipment. Read the Operator's Guide and watch the Safety DVD before driving. BRP highly recommends that all-terrain vehicle (ATV) drivers take a training course. ATVs can be hazardous to operate. For both ATVs and side-by-side vehicles (SSVs), the operator and passenger should wear a helmet, eye protection and other protective clothing. Respect the minimum age as required by law. For SSVs, fasten lateral net and seat belt at all times and passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Never carry passengers on any ATV not specifically designated for such use. For ATVs, BRP recommends not to carry any passengers under the age of 12. Always remember that riding and alcohol/drugs don't mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. Ride responsibly. BRP urges you to "TREAD LIGHTLY" on public and private lands. Preserve your future riding opportunities by showing respect for the environment, local laws and the rights of others when you ride. Always ride responsibly and safely. Never carry passengers on any ATV not specifically designated for such use. Highly skilled operators under controlled conditions appear in this brochure. Do not attempt these maneuvers if they are beyond your skill level. Pictures taken outward, on private land. Printed in Canada.

Can-am®



OUTLANDER™ MAX

SPECIFICATIONS OUTLANDER MAX 650 EFI

ENGINE	<p>Type Bore & Stroke Net Power Carburation/EFI Starting System Transmission Drive Train CO Emissions</p>	<p>649.6cc, V-twin, liquid-cooled, SOHC, 8-valve (4-valve/cyl) 82 x 62 mm < 15kW (EC version only) 46 mm Throttle Body, Siemens' VDO injector Electric CVT, sub-transmission with high, low, park, neutral & reverse Standard engine braking Selectable 2w/4w shaft driven with Visco-lok[†] front differential Euro-2 approved</p>
CHASSIS	<p>Frame Front Suspension Type/Shocks Front Suspension Travel Rear Suspension Type/Shocks Rear Suspension Travel Front Brake Rear Brake Tires/Front Tires/Rear Wheels</p>	<p>SST™ Double A-arm 203 mm (8 in) TTI™ independent 229 mm (9 in) 2 inboard hydraulic discs 1 inboard hydraulic disc 660 x 203 x 305 mm 26 x 8 x 12 in 660 x 254 x 305 mm 26 x 10 x 12 in Cast aluminum</p>
DIMENSIONS	<p>L x W x H (mm) L x W x H (in) Wheelbase Seat Height Ground Clearance Dry Weight Towing Capacity Rack Capacity Storage Fuel Capacity</p>	<p>2,387 x 1,168 x 1,143 mm 94 x 46 x 45 in 1,499 mm (59 in) 877 mm (34.5 in) 305 mm (12 in) 326 kg (719 lbs) 590 kg (1,300 lbs) Front: 45 kg (100 lbs) Rear: 90 kg (200 lbs) Rear storage 20L (5.3 US gal) CRS (Convertible Rack System) 16.3L (4.3 US gal)</p>
FEATURES	<p>Instrumentation Anti-Theft System Electrical Lighting DC Outlet Warning Signal Color Available</p>	<p>Multi-function digital LCD gauge: Speedometer, tachometer (bar graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4x4 indicator, temperature and engine lights, fuel gauge, clock, auto shut off after 15 minutes D.E.S.S.™ (Digital Encoded Security System) Prewired for winch 2 fender mounted headlamps (35W) with tail light/brake light Lighter type in console, standard connector in the back (15A) Horn Viper Red</p>
AVAILABLE PACKAGES	<p>XT PACKAGE CONTENT Color Available for XT</p>	<p>Dual-mode Dynamic Power Steering (DPS™) Visco-Lok QE XT cast aluminum wheels 650 watts magneto BRP XL3000 winch with roller fairlead and wired remote control Aggressive Carlisle[‡] ACT Radial tires Heavy-duty front & rear bumpers Handlebar wind deflectors Yellow and Camo</p>



OUTLANDER MAX 650 EFI



OUTLANDER MAX 650 EFI XT™

■ EC versions features

© 2010 Bombardier Recreational Products Inc (BRP). All rights reserved. ®, ™ and the BRP logo are registered trademarks of BRP or its affiliates. †Visco-Lok is a trademark of GKN Viscodrive GmbH. ‡All other trademarks are the property of their respective owners. Specifications for EC homologated units may differ slightly from specifications mentioned herein. Some models, tires and accessories depicted may not be available in your country. Depending on location, products are distributed by BRP European Distribution SA, BRP US Inc., BRP Australia Pty Ltd, or Bombardier Recreational Products Inc. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Some models depicted may include optional equipment. Read the Operator's Guide and watch the Safety DVD before driving. BRP highly recommends that all-terrain vehicle (ATV) drivers take a training course. ATVs can be hazardous to operate. For both ATVs and side-by-side vehicles (SSVs), the operator and passenger should wear a helmet, eye protection and other protective clothing. Respect the minimum age as required by law. For SSVs, fasten lateral net and seat belt at all times and passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Never carry passengers on any ATV not specifically designated for such use. For ATVs, BRP recommends not to carry any passengers under the age of 12. Always remember that riding and alcohol/drugs don't mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. Ride responsibly. BRP urges you to "TREAD LIGHTLY" on public and private lands. Preserve your future riding opportunities by showing respect for the environment, local laws and the rights of others when you ride. Always ride responsibly and safely. Never carry passengers on any ATV not specifically designated for such use. Highly skilled operators under controlled conditions appear in this brochure. Do not attempt these manoeuvres if they are beyond your skill level. Pictures taken outward, on private land. Printed in Canada.

can-am



OUTLANDER™ MAX

SPECIFICATIONS OUTLANDER MAX 800R EFI*

ENGINE	Type Bore & Stroke Net Power Carburation/EFI Starting System Transmission Drive Train CO Emissions	799.9cc, V-twin, liquid-cooled, SOHC, 8-valve (4-valve/cyl) 91 x 62 mm < 15kW (EC version only) 46 mm Throttle Body, 2 Siemens' VDO injectors Electric CVT, sub-transmission with high, low, park, neutral & reverse Standard engine braking Selectable 2w/4w shaft driven with Visco-lok ¹ front differential Euro-2 approved
CHASSIS	Frame Front Suspension Type/Shocks Front Suspension Travel Rear Suspension Type/Shocks Rear Suspension Travel Front Brake Rear Brake Tires/Front Tires/Rear Wheels	SST™ Double A-arm 203 mm (8 in) TTI™ independent 229 mm (9 in) 2 inboard hydraulic discs 1 inboard hydraulic disc 660 x 203 x 305 mm 26 x 8 x 12 in 660 x 254 x 305 mm 26 x 10 x 12 in Cast aluminum
DIMENSIONS	L x W x H (mm) L x W x H (in) Wheelbase Seat Height Ground Clearance Dry Weight Towing Capacity Rack Capacity Storage Fuel Capacity	2,387 x 1,168 x 1,143 mm 94 x 46 x 45 in 1,499 mm (59 in) 877 mm (34.5 in) 305 mm (12 in) 326 kg (719 lbs) 590 kg (1,300 lbs) Front: 45 kg (100 lbs) Rear: 90 kg (200 lbs) Rear storage 20L (5.3 US gal) CRS (Convertible Rack System) 16.3L (4.3 US gal)
FEATURES	Instrumentation Anti-Theft System Electrical Lighting DC Outlet Warning Signal Color Available	Multi-function digital LCD gauge: Speedometer, tachometer (bar graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4x4 indicator, temperature and engine lights, fuel gauge, clock, auto shut off after 15 minutes D.E.S.S.™ (Digital Encoded Security System) Prewired for winch 2 fender mounted headlamps (35W) with tail light/brake light Lighter type in console, standard connector in the back (15A) Horn
AVAILABLE PACKAGES	XT PACKAGE CONTENT Color Available for XT	Dual-mode Dynamic Power Steering (DPS™), Visco-Lok QE, XT cast aluminum wheels, 650 watts magneto, BRP XL3000 winch with roller fairlead and wired remote control, aggressive Carlisle [®] ACT Radial tires, heavy-duty front & rear bumpers, handlebar wind deflectors Yellow
	XT-P PACKAGE CONTENT Color Available for XT-P	Dual-mode Dynamic Power Steering (DPS), Visco-Lok QE, XT black cast aluminum wheels with color-matched inserts, 650 watts magneto, painted plastics, mud guards, BRP XL3000 winch with roller fairlead and wired remote control, aggressive Carlisle ACT Radial tires, heavy-duty front & rear bumpers, handlebar wind deflectors Black with steel grey metallic paint
	LTD PACKAGE CONTENT Color Available for LTD	Garmin [®] Nuvi [®] 500 touch screen GPS, Air Control rear Suspension (ACS), Dual-mode Dynamic Power Steering (DPS), Visco-Lok QE, LTD cast aluminum wheels, 650 watts magneto, BRP XL3000 winch with roller fairlead and wired remote control, painted plastics, aggressive Carlisle ACT radial tires, heavy-duty front & rear bumpers, mudguards, handlebar wind deflectors, premium 2-tone seat, comfort grips, chrome muffler trim Orbital Blue metallic paint



OUTLANDER MAX 800R EFI XT™



OUTLANDER MAX 800R EFI XT-P™



OUTLANDER MAX 800R EFI LTD

■ EC versions features

*Standard Outlander MAX 800R EFI model non available

© 2010 Bombardier Recreational Products Inc (BRP). All rights reserved. ®, ™ and the BRP logo are registered trademarks of BRP or its affiliates. ¹Visco-Lok is a trademark of GKN Viscodrive GmbH. †All other trademarks are the property of their respective owners. Specifications for EC homologated units may differ slightly from specifications mentioned herein. Some models, tires and accessories depicted may not be available in your country. Depending on location, products are distributed by BRP European Distribution SA, BRP US Inc., BRP Australia Pty Ltd, or Bombardier Recreational Products Inc. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Some models depicted may include optional equipment. Read the Operator's Guide and watch the Safety DVD before driving. BRP highly recommends that all-terrain vehicle (ATV) drivers take a training course. ATVs can be hazardous to operate. For both ATVs and side-by-side vehicles (SSVs), the operator and passenger should wear a helmet, eye protection and other protective clothing. Respect the minimum age as required by law. For SSVs, fasten lateral net and seat belt at all times and passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Never carry passengers on any ATV not specifically designated for such use. For ATVs, BRP recommends not to carry any passengers under the age of 12. Always remember that riding and alcohol/drugs don't mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. Ride responsibly. BRP urges you to "TREAD LIGHTLY" on public and private lands. Preserve your future riding opportunities by showing respect for the environment, local laws and the rights of others when you ride. Always ride responsibly and safely. Never carry passengers on any ATV not specifically designated for such use. Highly skilled operators under controlled conditions appear in this brochure. Do not attempt these manoeuvres if they are beyond your skill level. Pictures taken outdoors, on private land. Printed in Canada.

