



	SPECIFICATIONS	OUTLANDER 400 EFI	OUTLANDER 500 EFI
ENGINE	<p>Type</p> <p>Bore & Stroke</p> <p>Net Power</p> <p>Carburation/EFI</p> <p>Starting System</p> <p>Transmission</p> <p>Drive Train</p> <p>CO Emissions</p>	<p>400cc, single cylinder, liquid-cooled, SOHC, 4-valve</p> <p>91 x 61.5 mm</p> <p>< 15kW (EC version only)</p> <p>46 mm Throttle Body, Siemens VDO injectors</p> <p>Electric</p> <p>CVT, sub-transmission with high, low, park, neutral & reverse</p> <p>Standard engine braking</p> <p>Selectable 2w/4w shaft driven with Visco-lok[†] front differential</p> <p>Euro-2 approved</p>	<p>499.6cc, V-twin, liquid-cooled, SOHC, 8-valve (4-valve/cyl)</p> <p>82 x 47 mm</p> <p>< 15kW (EC version only)</p> <p>46 mm Throttle Body, 2 Siemens VDO injectors</p> <p>Electric</p> <p>CVT, sub-transmission with high, low, park, neutral & reverse</p> <p>Standard engine braking</p> <p>Selectable 2w/4w shaft driven with Visco-lok front differential</p> <p>Euro-2 approved</p>
CHASSIS	<p>Frame</p> <p>Front Suspension Type/Shocks</p> <p>Front Suspension Travel</p> <p>Rear Suspension Type/Shocks</p> <p>Rear Suspension Travel</p> <p>Front Brake</p> <p>Rear Brake</p> <p>Tires/Front</p> <p>Tires/Rear</p> <p>Wheels</p>	<p>SST™</p> <p>MacPherson[‡]</p> <p>178 mm (7 in)</p> <p>TTI™ independent</p> <p>203 mm (8 in)</p> <p>2 inboard hydraulic discs</p> <p>1 inboard hydraulic disc</p> <p>635 x 203 x 305 mm</p> <p>25 x 8 x 12 in</p> <p>635 x 279 x 305 mm</p> <p>25 x 11 x 12 in</p> <p>Steel</p>	<p>SST</p> <p>MacPherson</p> <p>178 mm (7 in)</p> <p>TTI independent</p> <p>229 mm (9 in)</p> <p>2 inboard hydraulic discs</p> <p>1 inboard hydraulic disc</p> <p>635 x 203 x 305 mm</p> <p>25 x 8 x 12 in</p> <p>635 x 279 x 305 mm</p> <p>25 x 10 x 12 in</p> <p>Cast aluminum</p>
DIMENSIONS	<p>L x W x H (mm)</p> <p>L x W x H (in)</p> <p>Wheelbase</p> <p>Seat Height</p> <p>Ground Clearance</p> <p>Dry Weight</p> <p>Towing Capacity</p> <p>Rack Capacity</p> <p>Storage</p> <p>Fuel Capacity</p>	<p>2,184 x 1,168 x 1,143 mm</p> <p>86 x 46 x 45 in</p> <p>1,244 mm (49 in)</p> <p>889 mm (35 in)</p> <p>236 mm (9.3 in)</p> <p>286 kg (630 lbs)</p> <p>500 kg (1,100 lbs)</p> <p>Front: 45 kg (100 lbs)</p> <p>Rear: 90 kg (200 lbs)</p> <p>Rear storage 20L (5.3 US gal)</p> <p>16.3L (4.3 US gal)</p>	<p>2,184 x 1,168 x 1,143 mm</p> <p>86 x 46 x 45 in</p> <p>1,295 mm (51 in)</p> <p>877 mm (34.5 in)</p> <p>279 mm (11 in)</p> <p>297 kg (654 lbs)</p> <p>590 kg (1,300 lbs)</p> <p>Front: 45 kg (100 lbs)</p> <p>Rear: 90 kg (200 lbs)</p> <p>Rear storage 20L (5.3 US gal)</p> <p>16.3L (4.3 US gal)</p>
FEATURES	<p>Instrumentation</p> <p>Anti-Theft System</p> <p>Electrical</p> <p>Lighting</p> <p>DC Outlet</p> <p>Warning Signal</p> <p>Color Available</p>	<p>Multi-function digital LCD gauge: Speedometer, tachometer (bar graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4x4 indicator, temperature and engine lights, fuel gauge, clock, auto shut off after 15 minutes</p> <p>D.E.S.S.™ (Digital Encoded Security System)</p> <p>Prewired for winch</p> <p>2 fender mounted headlamps (35W) with tail light/brake light</p> <p>Lighter type in console, standard connector in the back (15A)</p> <p>Horn</p> <p>Viper Red</p>	<p>Multi-function digital LCD gauge: Speedometer, tachometer (bar graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4x4 indicator, temperature and engine lights, fuel gauge, clock, auto shut off after 15 minutes</p> <p>D.E.S.S. (Digital Encoded Security System)</p> <p>Prewired for winch</p> <p>2 fender mounted headlamps (35W) with tail light/brake light</p> <p>Lighter type in console, standard connector in the back (15A)</p> <p>Horn</p> <p>Viper Red</p>
AVAILABLE PACKAGES	<p>XT PACKAGE CONTENT</p> <p>Color Available for XT</p>		<p>Dual-mode Dynamic Power Steering (DPS™), Visco-Lok QE, XT cast aluminum wheels, 650 Watts magneto, BRP XL3000 winch with roller fairlead and wired remote control, aggressive Carlisle[®] ACT Radial tires, heavy-duty front & rear bumpers, handlebar wind deflectors</p> <p>Yellow</p>



OUTLANDER 400 EFI



OUTLANDER 500 EFI

EC version non available



OUTLANDER 500 EFI XT™

■ EC versions features

© 2010 Bombardier Recreational Products Inc (BRP). All rights reserved. ®, ™ and the BRP logo are registered trademarks of BRP or its affiliates. †Visco-Lok is a trademark of GKN ViscoDrive GmbH. ‡All other trademarks are the property of their respective owners. Specifications for EC homologated units may differ slightly from specifications mentioned herein. Some models, tires and accessories depicted may not be available in your country. Depending on location, products are distributed by BRP European Distribution SA, BRP US Inc., BRP Australia Pty Ltd, or Bombardier Recreational Products Inc. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Some models depicted may include optional equipment. Read the Operator's Guide and watch the Safety DVD before driving. BRP highly recommends that all-terrain vehicle (ATV) drivers take a training course. ATVs can be hazardous to operate. For both ATVs and side-by-side vehicles (SSVs), the operator and passenger should wear a helmet, eye protection and other protective clothing. Respect the minimum age as required by law. For SSVs, fasten lateral net and seat belt at all times and passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Never carry passengers on any ATV not specifically designated for such use. For ATVs, BRP recommends not to carry any passengers under the age of 12. Always remember that riding and alcohol/drugs don't mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. Ride responsibly. BRP urges you to "TREAD LIGHTLY" on public and private lands. Preserve your future riding opportunities by showing respect for the environment, local laws and the rights of others when you ride. Always ride responsibly and safely. Never carry passengers on any ATV not specifically designated for such use. Highly skilled operators under controlled conditions appear in this brochure. Do not attempt these manoeuvres if they are beyond your skill level. Pictures taken outdoors, on private land. Printed in Canada.



SPECIFICATIONS OUTLANDER 650 EFI

ENGINE	Type Bore & Stroke Net Power Carburation/EFI Starting System Transmission Drive Train CO Emissions	649.6cc, V-twin, liquid-cooled, SOHC, 8-valve (4-valve/cyl) 82 x 62 mm < 15kW (EC version only) 46 mm Throttle Body, 2 Siemens [†] VDO injectors Electric CVT, sub-transmission with high, low, park, neutral & reverse. Standard engine braking Selectable 2w/4w shaft driven with Visco-lok [†] front differential Euro-2 approved
CHASSIS	Frame Front Suspension Type/Shocks Front Suspension Travel Rear Suspension Type/Shocks Rear Suspension Travel Front Brake Rear Brake Tires/Front Tires/Rear Wheels	SST™ Double A-arm 203 mm (8 in) TTI™ independent 229 mm (9 in) 2 inboard hydraulic discs 1 inboard hydraulic disc 660 x 203 x 305 mm 26 x 8 x 12 in 660 x 254 x 305 mm 26 x 10 x 12 in Cast aluminum
DIMENSIONS	L x W x H (mm) L x W x H (in) Wheelbase Seat Height Ground Clearance Dry Weight Towing Capacity Rack Capacity Storage Fuel Capacity	2,184 x 1,168 x 1,143 mm 86 x 46 x 45 in 1,295 mm (51 in) 877 mm (34.5 in) 305 mm (12 in) 303 kg (669 lbs) 590 kg (1,300 lbs) Front: 45 kg (100 lbs) Rear: 90 kg (200 lbs) Rear storage 20L (5.3 US gal) 16.3L (4.3 US gal)
FEATURES	Instrumentation Anti-Theft System Electrical Lighting DC Outlet Warning Signal Color Available	Multi-function digital LCD gauge: Speedometer, tachometer (bar graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4x4 indicator, temperature and engine lights, fuel gauge, clock, auto shut off after 15 minutes D.E.S.S.™ (Digital Encoded Security System) Prewired for winch 2 fender mounted headlamps (35W) with tail light/brake light Lighter type in console, standard connector in the back (15A) Horn Viper Red
AVAILABLE PACKAGES	XT PACKAGE CONTENT Color Available for XT	Dual-mode Dynamic Power Steering (DPS™), Visco-Lok QE, XT cast aluminum wheels, 650 watts magneto, BRP XL3000 winch with roller fairlead and wired remote control, aggressive Carlisle [‡] ACT Radial tires, heavy-duty front & rear bumpers, handlebar wind deflectors Yellow



OUTLANDER 650 EFI



OUTLANDER 650 EFI XT™

■ EC versions features

© 2010 Bombardier Recreational Products Inc (BRP). All rights reserved. ®, ™ and the BRP logo are registered trademarks of BRP or its affiliates. †Visco-Lok is a trademark of GKN Viscodrive GmbH. ‡All other trademarks are the property of their respective owners. Specifications for EC homologated units may differ slightly from specifications mentioned herein. Some models, tires and accessories depicted may not be available in your country. Depending on location, products are distributed by BRP European Distribution SA, BRP US Inc., BRP Australia Pty Ltd, or Bombardier Recreational Products Inc. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Some models depicted may include optional equipment. Read the Operator's Guide and watch the Safety DVD before driving. BRP highly recommends that all-terrain vehicle (ATV) drivers take a training course. ATVs can be hazardous to operate. For both ATVs and side-by-side vehicles (SSVs), the operator and passenger should wear a helmet, eye protection and other protective clothing. Respect the minimum age as required by law. For SSVs, fasten lateral net and seat belt at all times and passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Never carry passengers on any ATV not specifically designated for such use. For ATVs, BRP recommends not to carry any passengers under the age of 12. Always remember that riding and alcohol/drugs don't mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. Ride responsibly. BRP urges you to "TREAD LIGHTLY" on public and private lands. Preserve your future riding opportunities by showing respect for the environment, local laws and the rights of others when you ride. Always ride responsibly and safely. Never carry passengers on any ATV not specifically designated for such use. Highly skilled operators under controlled conditions appear in this brochure. Do not attempt these manoeuvres if they are beyond your skill level. Pictures taken outward, on private land. Printed in Canada.



SPECIFICATIONS		OUTLANDER 800R EFI*
ENGINE	Type	799.9cc, V-twin, liquid-cooled, SOHC, 8-valve (4-valve/cyl)
	Bore & Stroke	91 x 62 mm
CHASSIS	Net Power	<15kW (EC version only)
	Carburation/EFI	46 mm Throttle Body, 2 Siemens' VDO injectors
	Starting System	Electric
	Transmission	CVT, sub-transmission with high, low, park, neutral & reverse. Standard engine braking
	Drive Train	Selectable 2w/4w shaft driven with Visco-lokt front differential
	CO2 emissions	Euro-2 approved
	Frame	SST™
	Front Suspension Type/Shocks	Double A-arm
	Front Suspension Travel	203 mm (8 in)
	Rear Suspension Type/Shocks	TTI™ independent
Rear Suspension Travel	229 mm (9 in)	
Front Brake	2 inboard hydraulic discs	
Rear Brake	1 inboard hydraulic disc	
Tires/Front	660 x 203 x 305 mm 26 x 8 x 12 in	
Tires/Rear	660 x 254 x 305 mm 26 x 10 x 12 in	
Wheels	Cast aluminum	
DIMENSIONS	L x W x H (mm)	2,184 x 1,168 x 1,143 mm
	L x W x H (in)	86 x 46 x 45 in
	Wheelbase	1,295 mm (51 in)
	Seat Height	877 mm (34.5 in)
	Ground Clearance	305 mm (12 in)
	Dry Weight	303 kg (669 lbs)
	Towing Capacity	590 kg (1,300 lbs)
	Rack Capacity	Front: 45 kg (100 lbs) Rear: 90 kg (200 lbs)
	Storage	Rear storage 20L (5.3 US gal)
	Fuel Capacity	16.3L (4.3 US gal)
FEATURES	Instrumentation	Multi-function digital LCD gauge: Speedometer, tachometer (Net Power, bar graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4x4 indicator, temperature and engine lights, fuel gauge, auto shut off after 15 minutes, clock
	Anti-Theft System	D.E.S.S.™ (Digital Encoded Security System)
	Electrical	Prewired for winch
	Lighting	2 fender mounted headlamps (35W) with tail light/brake light
	DC Outlet	Lighter type in console, standard connector in the back (15A)
	Warning Signal	Horn
AVAILABLE PACKAGES	XT PACKAGE CONTENT	Dual-mode Dynamic Power Steering (DPS™), Visco-Lok QE, XT cast aluminum wheels, 650 watts magneto, BRP XL3000 winch with roller fairlead and wired remote control, aggressive Carlisle [‡] ACT Radial tires, heavy-duty front & rear bumpers, handlebar wind deflectors
	Color Available for XT	Yellow
	XT-P PACKAGE CONTENT	Dual-mode Dynamic Power Steering (DPS), Visco-Lok QE, XT-P black cast aluminum wheels with color-matched inserts, 650 watts magneto, Painted plastics, mud guards, BRP XL3000 winch with roller fairlead and wired remote control, aggressive Carlisle ACT Radial tires, heavy-duty front & rear bumpers, handlebar wind deflectors
	Color Available for XT-P	Black with steel grey metallic paint
X xc PACKAGE CONTENT	Dual-mode Dynamic Power Steering (DPS), Beadlock wheels, ITP Holeshot [†] ATR sport radial tires, Front KYB [‡] HPG shocks with dual-speed compression, rebound and threaded preload adjustments, Rear KYB HPG shocks with remote reservoir with dual-speed compression, rebound and threaded preload adjustments, Front sway bar, Visco-Lok QE, Pre-runner type front bumper, Aluminum skid plate, Aluminum taper-profile handlebar with wind deflectors, 650 watt magneto, X xc -package coloration, graphics and seat cover	
Color available for Xxc	Yellow & black with X package graphics	
X mr PACKAGE CONTENT	Front and rear Air Control Suspension (ACS), 30-inch (76.2 cm) Gorilla Axle Silverback tires, 14-inch (35.6 cm) ITP cast-aluminum wheels, Dual-mode Dynamic Power Steering (DPS), Integrated Snorkel System (ISS), Relocated radiator, Visco-Lok QE, BRP XL3000 winch with roller fairlead and wired, remote control, Aluminum taper-profile handlebar with wind deflectors, Mudguards, Mud-riding footrests, Longer wheelbase, X mr-package coloration, graphics and seat cover	
Color available for Xmr	Yellow & black with X package graphics	



OUTLANDER 800R EFI XT

EC version non available



OUTLANDER 800R EFI XT-P™



OUTLANDER 800R EFI X xc



OUTLANDER 800R EFI X mr

EC version non available

*Standard Outlander 800R EFI EC model non available

© 2010 Bombardier Recreational Products Inc (BRP). All rights reserved. ®, ™ and the BRP logo are registered trademarks of BRP or its affiliates. †Visco-Lok is a trademark of GKN Viscodrive GmbH. ‡All other trademarks are the property of their respective owners. Specifications for EC homologated units may differ slightly from specifications mentioned herein. Some models, tires and accessories depicted may not be available in your country. Depending on location, products are distributed by BRP European Distribution SA, BRP US Inc., BRP Australia Pty Ltd. or Bombardier Recreational Products Inc. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Some models depicted may include optional equipment. Read the Operator's Guide and watch the Safety DVD before driving. BRP highly recommends that all-terrain vehicle (ATV) drivers take a training course. ATVs can be hazardous to operate. For both ATVs and side-by-side vehicles (SSVs), the operator and passenger should wear a helmet, eye protection and other protective clothing. Respect the minimum age as required by law. For SSVs, fasten lateral net and seat belt at all times and passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Never carry passengers on any ATV not specifically designated for such use. For ATVs, BRP recommends not to carry any passengers under the age of 12. Always remember that riding and alcohol/drugs don't mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. Ride responsibly. BRP urges you to "TREAD LIGHTLY" on public and private lands. Preserve your future riding opportunities by showing respect for the environment, local laws and the rights of others when you ride. Always ride responsibly and safely. Never carry passengers on any ATV not specifically designated for such use. Highly skilled operators under controlled conditions appear in this brochure. Do not attempt these manoeuvres if they are beyond your skill level. Pictures taken outward, on private land. Printed in Canada.