

	SPECIFICATIONS	RENEGADE 500 EFI	RENEGADE 800R EFI
ENGINE	Type	499.6cc, V-twin, liquid-cooled, SOHC, 8-valve (4-valve/cyl)	799.9cc, V-twin, liquid-cooled, SOHC, 8-valve (4-valve/cyl)
	Bore & Stroke	82 x 47 mm	91 x 62 mm
CHASSIS	Net Power	< 15kW (EC version only)	< 15kW (EC version only)
	Carburation/EFI	46 mm Throttle Body, Siemens VDO injectors	46 mm Throttle Body, 2 Siemens VDO injectors
	Starting System	Electric	Electric
	Transmission	CVT, sub-transmission with high, low, park, neutral & reverse	CVT, sub-transmission with high, low, park, neutral & reverse
	Standard engine braking	Standard engine braking	Standard engine braking
	Drive Train	Selectable 2w/4w shaft driven with Visco-lok [†] front differential	Selectable 2w/4w shaft driven with Visco-lok front differential
	CO Emissions	Euro-2 approved	Euro-2 approved
	Frame	SST™	SST
	Front Suspension Type/Shocks	RS-Type Double A-arm, Motion Control shocks	RS-Type Double A-arm, HPG shocks
	Front Suspension Travel	216 mm (8.5 in)	216 mm (8.5 in)
Rear Suspension Type/Shocks	RS-Type TTI™ independent/Motion Control shocks	RS-Type TTI independent/HPG shocks	
Rear Suspension Travel	229 mm (9 in)	229 mm (9 in)	
Front Brake	2 hydraulic discs	2 hydraulic discs	
Rear Brake	1 inboard hydraulic disc	1 inboard hydraulic disc	
Tires/Front	ITP Holeshoot [‡] ATR 635 x 203 x 305 mm 25 x 8 x 12 in	ITP Holeshoot ATR 635 x 203 x 305 mm 25 x 8 x 12 in	
Tires/Rear	ITP Holeshoot ATR 635 x 254 x 305 mm 25 x 10 x 12 in	ITP Holeshoot ATR 635 x 254 x 305 mm 25 x 10 x 12 in	
Wheels	Center cast aluminum	Center cast aluminum	
DIMENSIONS	L x W x H (mm)	2,184 x 1,168 x 1,143 mm	2,184 x 1,168 x 1,143 mm
	L x W x H (in)	86 x 46 x 45 in	86 x 46 x 45 in
	Wheelbase	1,295 mm (51 in)	1,295 mm (51 in)
	Seat Height	877 mm (34.5 in)	877 mm (34.5 in)
	Ground Clearance	279 mm (11 in)	279 mm (11 in)
	Dry Weight	279 kg (614 lbs)	279 kg (614 lbs)
	Towing Capacity	590 kg (1,300 lbs)	590 kg (1,300 lbs)
	Rack Capacity	16 kg (35 lbs)	16 kg (35 lbs)
	Storage	Rear storage 3.7L (1 US gal)	Rear storage 3.7L (1 US gal)
	Fuel Capacity	16.3L (4.3 US gal)	16.3L (4.3 US gal)
FEATURES	Instrumentation	Multi-function gauge: Speedometer, tachometer, odometer, trip and hourmeters, fuel, gear position, 4x4 indicator, diagnostics, clock, auto shut off	Multi-function gauge: Speedometer, tachometer, odometer, trip and hourmeters, fuel, gear position, 4x4 indicator, diagnostics, clock, auto shut off
	Anti-Theft System	D.E.S.S.™ (Digital Encoded Security System)	D.E.S.S. (Digital Encoded Security System)
	Electrical	Prewired for winch	Prewired for winch
	Lighting	4 fender mounted Projector Beam headlamps (60W) with tail light/brake light	4 fender mounted Projector Beam headlamps (60W) with tail light/brake light
	DC Outlet	Lighter type in console, standard connector in the back (15A)	Lighter type in console, standard connector in the back (15A)
	Warning Signal	Horn	Horn
Color Available	White	White	
AVAILABLE PACKAGES	X xc PACKAGE CONTENT		Dual-mode Dynamic Power Steering (DPS™), Visco-Lok QE, Beadlock wheels, front sway bar, 650 watts magneto, front KYB [‡] HPG aluminum piggyback shocks with dual speed compression, rebound and preload adjustments, rear KYB HPG with remote reservoir shocks with dual speed compression, rebound and preload adjustments, aluminum skid plate, handlebar wind deflectors, aluminum taper-profile handlebar with square pad, xc package graphics and seat cover
	Color Available for X xc		Yellow & black with X package graphics



RENEGADE 500 EFI



RENEGADE 800R EFI



RENEGADE 800R EFI Xc

■ EC versions features

© 2010 Bombardier Recreational Products Inc (BRP). All rights reserved. ®, ™ and the BRP logo are registered trademarks of BRP or its affiliates. †Visco-Lok is a trademark of GKN ViscoDrive GmbH. ‡All other trademarks are the property of their respective owners. Specifications for EC homologated units may differ slightly from specifications mentioned herein. Some models, tires and accessories depicted may not be available in your country. Depending on location, products are distributed by BRP European Distribution SA, BRP US Inc., BRP Australia Pty Ltd, or Bombardier Recreational Products Inc. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Some models depicted may include optional equipment. Read the Operator's Guide and watch the Safety DVD before driving. BRP highly recommends that all-terrain vehicle (ATV) drivers take a training course. ATVs can be hazardous to operate. For both ATVs and side-by-side vehicles (SSVs), the operator and passenger should wear a helmet, eye protection and other protective clothing. Respect the minimum age as required by law. For SSVs, fasten lateral net and seat belt at all times and passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Never carry passengers on any ATV not specifically designated for such use. For ATVs, BRP recommends not to carry any passengers under the age of 12. Always remember that riding and alcohol/drugs don't mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. Ride responsibly. BRP urges you to "TREAD LIGHTLY" on public and private lands. Preserve your future riding opportunities by showing respect for the environment, local laws and the rights of others when you ride. Always ride responsibly and safely. Never carry passengers on any ATV not specifically designated for such use. Highly skilled operators under controlled conditions appear in this brochure. Do not attempt these manoeuvres if they are beyond your skill level. Pictures taken outdoors, on private land. Printed in Canada.