SPECIFICATIONS

Туре

249.4cc, single cylinder, liquid-cooled, SOHC, 4-valve

Bore & Stroke 71 x 63 mm

< 15kW (EC version only)

DS 250

Net Power Carburetion/EFI

Keihin[‡] PTG 23

Starting System Transmission

Automatic CVT, sub-transmission w/forward,

neutral & reverse

Drive Train CO Emissions

Chain driven/solid axle Euro-2 approved

Electric

Frame Front Suspension Type/Shocks

Front Suspension Travel Rear Suspension Type/Shocks

Rear Suspension Travel Front Brake Rear Brake

1 hydraulic disc

Tyres/Front Tyres/Rear

Wheels

LxWxH(mm) L x W x H (in) Wheelbase Seat Height

1,187 mm (47 in) 800 mm (31.5 in)

Ground Clearance Dry Weight

Fuel Capacity

Instrumentation Lighting DC Outlet

Yes

Warning Signal Colour Available

DS 250

Double A-arm

5-position adjustable pre-load

140 mm (5.5 in) Swingarm

5-position adjustable pre-load

170 mm (6.7 in) 2 hydraulic discs 559 x 178 x 254 mm 22 x 7 x 10 in

508 x 279 x 229 mm 20 x 11 x 9 in

72 x 40.5 x 43.5 in 1,830 x 1,030 x 1,105 mm

260 mm (10.2 in) Center of ATV

429 lbs (195 kg) 12.5L

Neutral light, reverse light and oil/temperature light 2 headlamps (35W) with tail light/brake light

Horn Yellow

■ EC versions features



DS 250